

# Series WTW-LS 20 (IP64)



The portable light weight dual axis auto tracking antenna.



The WTW LSC Tracking Antennas are developed in according to the latest technology to fulfil compactness, last technology, low weight and high efficiency.



This is possible with more than 30 years experienced personal in developing robust and long-lasting mechanics and excellent RF features.

## KEY FEATURES

- Weight: appr. 24 kg
- Dimension (Park Position El. 90°): appr. 27.5" x 16" x 23" (WxDxH)
- Dimension (Transport Position El. 0°): appr. 27.5" x 15" x 22" (WxDxH)
- Polarisation: RHCP und LHCP
- Mode:
  - Auto-, Slave-, Manual-Tracking
- Torque:
  - Az. max. 40 Nm
  - El. max. 69 Nm
- Speed:
  - Az. max. 60°/sec
  - El. max. 60°/sec
- Movement:
  - Az. unlimited (Slipping)
  - El. -5° up to 90°
- operational Windspeed: up to 65mph
- stowed: up to 100mph

### Option:

- C-Band



The WTW Anlagenbau GmbH is a premium manufacturer for telemetry antennas using the latest technology combined with ultimate performance for **Airplane, Helicopter, Missile and Rocket** test on **Land or Water**.

# Series WTW-LS 20 (IP64)



## Series WTW-LS 20

Reflector Size	25.5" x 15.5" (W x H)
Frequency Range	1400 MHz to 2485 MHz Optional C-Band
Gain	appr. 15 dBi @ 1850 MHz appr. 19 dBi @ 2350 MHz appr. 19 dBi @ 4650 MHz (Option) appr. 20 dBi @ 5100 MHz (Option)
Velocity Azimuth	max. 60°/sec
Velocity Elevation	max. 60°/sec
Acceleration Azimuth	max. 60°/sec <sup>2</sup>
Acceleration Elevation	max. 60°/sec <sup>2</sup>
Output Torque (max. intermittent)	40 Nm
Elevation Travel	-5° to 90°
Azimuth Travel	unlimited
Power Requirement	appr. 150 W
Temperature	-20°C to +70°C
Humidity	0 to 100%
Windspeed	Up to 65mph
Dimension in Park Position (WxDxH)	22.5" x 15.5" x 22"

## Options

Radom
Gimbel
Battery
Diesel Generator
Pedestal for Downconverter, Receiver, Dehydrator
Feet for mobile Application
Mobile Hydraulic Tower (up to 8m)

### National / International Sales / Marketing:

Tel Data System GmbH

Phone: +49 (0) 81 21 - 41 01 18

Email: [telemetrie@wtw-anlagenbau.de](mailto:telemetrie@wtw-anlagenbau.de)



### Germany Sales / Marketing:

artronics GmbH

Phone: +49 (0) 81 31 3624 - 0

Email: [telemetrie@wtw-anlagenbau.de](mailto:telemetrie@wtw-anlagenbau.de)



### US Sales / Marketing:

Rampart Defense Solutions LLC

Phone: +1 423.552.7064

Email: [Brenda@rampartds.com](mailto:Brenda@rampartds.com)



### WTW Anlagenbau GmbH

Gutenbergstrasse 3

26632 Ihlow-Riepe

Germany

Phone: +49 (0) 4928/914598-0

Fax: +49 (0) 4928/914598-9

Email: [telemetrie@wtw-anlagenbau.de](mailto:telemetrie@wtw-anlagenbau.de)

Web: [www.tracking-antenna.de](http://www.tracking-antenna.de)

The Power of German Engineering



DIN EN ISO 9001:2008

Rev. May 2017